

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier

1528A1NL

Product Name:

CARBOTHANE 134 CLEAR COAT PART

CLEAR COAT PART A

Component of Entified uses of the multicomponent industrial

Revision Date: Supercedes Date:

06/06/2023 12/06/2022

- 1.2 Relevant identified uses of the substance or mixture and uses advised against multicomponent industrial use.
- 1.3 Details of the supplier of the safety data sheet

	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146
		Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.com
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669

# 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Carcinogenicity, category 1A Eye Irritation, category 2 Flammable Liquid, category 2 Reproductive Toxicity, category 2

#### 2.2 Label elements

#### Symbol(s) of Product



Signal Word

Danger

#### Named Chemicals on Label

ETHYL BENZENE, TOLUENE, METHYL N-AMYL KETONE, TERT-BUTYL ACETATE

#### HAZARD STATEMENTS

Flammable Liquid, category 2 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Reproductive Toxicity, category 2 Hazardous to the aquatic environment, Chronic, category 3	H225 H319 H332 H350-1A H361 H412	Highly flammable liquid and vapour. Causes serious eye irritation. Harmful if inhaled. May cause cancer. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201 P202 P210 P235 P261 P273 P280 P284 P304+340 P305+351+338 P308+313 P403+233	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep cool. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/ face protection. Wear respiratory protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. IF exposed or concerned: Get medical advice/attention Store in a well-ventilated place. Keep container tightly
	P304+340 P305+351+338 P308+313	Wear respiratory protection. IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do so. Continue rinsing.

#### 2.3 Other hazards

No Information

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

#### 3.2 Mixtures

Hazardous ingredients					
Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	Classifications	
METHYL N-AMYL KETONE	203-767-1	110-43-0	10 - <25	H226-302-332	Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Flam. Liq. 3

DIMETHYL CARBONATE	210-478-4	616-38-6	10 - <25	H225	
TERT-BUTYL ACETATE	208-760-7	540-88-5	2.5 - <10	H225-332-335-336	
METHYL ETHYL KETONE	201-159-0	78-93-3	2.5 - <10	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
ALIPHATIC DIOL	203-489-0	PROPRIETA RY	2.5 - <10	H315-319	Eye Irrit. 2, Skin Irrit. 2
TOLUENE	203-625-9	108-88-3	2.5 - <10	H225-304-315-319-332-335-336 -361-370-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 1, STOT SE 3 NE, STOT SE 3 RTI
N-BUTYL ACETATE	204-658-1	123-86-4	1.0 - <2.5	H226-336	Flam. Liq. 3, STOT SE 3 NE
DEFOAMER	265-148-2	64742-46-7	0.1 - <1.0	H350	
ETHYL BENZENE	202-849-4	100-41-4	0.1 - <1.0	H225-304-315-319-332-351-373 -412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2

CAS-No.	M-Factors
110-43-0	0
616-38-6	0
540-88-5	0
78-93-3	0
PROPRIETARY	0
108-88-3	0
123-86-4	0
64742-46-7	0
100-41-4	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

### 4. First-aid Measures

#### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

### 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

No Information

### 7. Handling and Storage

#### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### CONDITIONS TO AVOID: Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

<u>۱</u>	-	-	/

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
METHYL N-AMYL KETONE	110-43-0	50 PPM	N/E	N/E
DIMETHYL CARBONATE	616-38-6	N/E	N/E	N/E
TERT-BUTYL ACETATE	540-88-5	50 PPM	150 PPM	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E
ALIPHATIC DIOL	PROPRIETARY	25 PPM	50 PPM	N/E
TOLUENE	108-88-3	20 PPM	N/E	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
DEFOAMER	64742-46-7	N/E	N/E	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
Name	CAS-No.	<u>OSHA PE</u>	<u>:L OSHA S</u>	<u>rel</u>
METHYL N-AMYL KETONE	110-43-0	465 MGM3,	100 PPM N/E	
DIMETHYL CARBONATE	616-38-6	N/E	N/E	
TERT-BUTYL ACETATE	540-88-5	950 MGM3,	200 PPM N/E	
METHYL ETHYL KETONE	78-93-3	590 MGM3,	200 PP <b>8⁄8</b> 5 MGM3 PPM	s, 300
ALIPHATIC DIOL	PROPRIETARY	N/E	N/E	
TOLUENE	108-88-3	200 ppm	560 MGM3 PPM	s, 150
N-BUTYL ACETATE	123-86-4	710 MGM3,	150 PP <b>9/5</b> 0 MGM3 PPM	s, 200
DEFOAMER	64742-46-7	N/E	N/E	
ETHYL BENZENE	100-41-4	435 MGM3,	100 PP <b>54</b> 5 MGM3 PPM	s, 125

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

#### EYE PROTECTION: Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	s Clear, Slightly Amber Liquid
	Physical State	Liquid
	Odor	Solvent
	Odor threshold	N/D
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	149 F (65 C) - 518 F (270 C)
	Flash Point (°C)	50
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	1.0 - 36.0
	Vapour Pressure, mmHg	N/D
	Vapour density	Heavier than Air
	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	240
	Specific Gravity (g/cm3)	0.99

# 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

#### 11.

1.1	Information on toxicological effe	ects
	Acute Toxicity:	
	Oral LD50:	N/D
	Inhalation LC50:	N/D
	Irritation:	Unknown
	Corrosivity:	Unknown
	Sensitization:	Unknown
	Repeated dose toxicity:	Unknown
	Carcinogenicity:	Unknown
	Mutagenicity:	Unknown
	Toxicity for reproduction:	Unknown
	STOT-single exposure:	No Information
	STOT-repeated exposure:	No Information
	Aspiration hazard:	No Information

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>(</u>	CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
	110-43-0	METHYL N-AMYL KETONE	1670 mg/kg rat oral	Not Available	2000 ppm, 4 hours	0.000	0.000
	616-38-6	DIMETHYL CARBONATE	12900 mg/kg, oral, rat	>2000 mg/kg, dermal, rabbit	Not Available	0.000	0.000
	540-88-5	TERT-BUTYL ACETATE	3160 mg/kg, oral, rat	Not Available	4000 ppm/6 hours, rat inhalation	0.000	0.000
	78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000

PROPRIETA Y	<sup>AR</sup> ALIPHATIC DIOL	Not Available		Not Available	0.000	0.000
108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation	No Information	No Information
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat	No Information	No Information
64742-46-7	DEFOAMER	>5000 mg/kg, rat, oral		NOT AVAILABLE	0.000	0.000
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	No Information	No Information

#### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

12.1 Toxic	ity:							
EC	50 48hr (Daphnia):	Unknov	vn					
IC	50 72hr (Algae):	Unknow	vn					
LC	50 96hr (fish):	Unknov	vn					
12.2 Persistence and degradability:		Unknow	vn					
12.3 Bioaccumulative potential:		Unknow	vn					
12.4 Mobility in soil:		Unknow	Unknown					
12.5 Results of PBT and vPvB assessment:		The pro	oduct does not meet the	e criteria for PBT/VPvB	in accordance with Annex			
12.6 Othe	r adverse effects:	Unknov	vn					
CAS-No.	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>			
110-43-0	METHYL N-AMYL KETONE		No information	No information	126 - 137 mg/L - Pimephale promelas			
616-38-6	DIMETHYL CARBONATE		100 mg/l (Daphnia magna)	100 mg/l (Algae)	100 mg/l (Zebra Fish)			
540-88-5	TERT-BUTYL ACETATE		No information	No information	No information			
78-93-3	METHYL ETHYL KETONE		308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)			
PROPRIETA Y	ARALIPHATIC DIOL		No information	No information	No information			
108-88-3	TOLUENE		6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)			
123-86-4	N-BUTYL ACETATE		44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)			
	DEFOAMER		No information	No information	No information			
64742-46-7								

# 13. Disposal Considerations

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	14. Transport Information				
14.1	UN number	UN 1263			
14.2	UN proper shipping name	Paint			
	Technical name	N/A			
14.3	Transport hazard class(es)	3			
	Subsidiary shipping hazard	N/A			
14.4	Packing group	П			
14.5	Environmental hazards	Unknown			
14.6	Special precautions for user	Unknown			
	EmS-No.:	F-E, S-E			
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown			

# 15. Regulatory Information

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Serious eye damage or eye irritation

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>	<u>)</u>
TOLUENE 108-88-3 3.	13
META-XYLENE 108-38-3 0.3	32
PARA-XYLENE 106-42-3 0.	14
ORTHO-XYLENE 95-47-6 0.	1
BENZENE 71-43-2 0	

#### **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

#### Chemical Name

CAS-No.

No TSCA 12(b) components exist in this product.

# U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
ACRYLIC COPOLYMER	TRADE SECRET
ACRYLIC POLYOL	TRADE SECRET
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
ACRYLIC COPOLYMER	TRADE SECRET
ACRYLIC POLYOL	TRADE SECRET
CALIFORNIA PROPOSITION 65	

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

### International Regulations: As follows -

#### \* Canadian DSL:

No Information

#### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Date Printed: 06/06/2023

Date Printed: 06/06/2023